

## GEOA084AU-LO01-DT 8.4" LCD Mount Touch monitors

### BENEFITS :

- Designed to give state-of-the-art picture quality
- Analog RGB / DVI (Digital Video Interface)
- Full CRT multi-sync monitor compatibility
- Single control operated & transparent On-Screen-Display (hereafter 'OSD') user interface
- Application
  - Casino and amusement games
  - Information kiosks
  - Self-service
  - Industrial process control

### SPECIFICATIONS

Model	GEOA084AU-LO01-DT
Case	Steel
Display Type	Size: 8.4" diagonal Type: Active matrix TFT LCD
Useful screen area	Horizontal: 170.4 mm Vertical: 127.8 mm
Monitor dimensions	Width: 214 mm Height: 148mm Depth: 30mm
Optimal (native) resolution	800 x 600
Other supported resolutions	640 x 350 at 70Hz 640 x 400 at 70Hz 720 x 350 at 70Hz 720 x 400 at 70Hz 640 x 480 at 60~75Hz 800 x 600 at 60~75Hz
Colors	6-bit, 262,144 colors
Brightness LCD panel	220 cd/m2(Typ.)/With out Touch
Response time	35 msec (typical)
Viewing angle (typical, from center)	Horizontal (left/right): ±65° or 130° total Vertical (up/down): ±65° or 110° total
Contrast ratio	500:1 (typical)
Input video format	Analog RGB , DVI
Input video signal connector	Mini D-Sub 15-Pin, DVI 24-Pin
Input frequency	Horizontal: 31.5–80 kHz Vertical: 60–75 Hz
Power supply	Type: External brick, 100–240 VAC, 50–60 Hz Monitor input voltage: 12 VDC
Temperature	Operating: 0°C to 50°C Storage: -20°C to 60°C
Humidity	Operating: 8%–90% Storage: 5%–90% noncondensing
Weight (approx.)	Actual: 0.8 kg Packing/10pcs: TBD Packing dimensions: TBD
Touch interface	USB included
Mounting options	Option

